
The Real Machine Learning Interview

100 Questions Based on Real Interview Patterns

Reader preview



Three complete answers from the book, including the practical explanations, follow-ups, common mistakes, and practice prompts. Original chapter and question numbers are retained.

Chapter 1, Q2 When ML is the wrong tool

Chapter 7, Q4 Monitoring drift without immediate labels

Chapter 9, Q7 Tracing a fabricated RAG answer

Read the answer aloud. The first paragraph is the version you should be able to say in an interview. The rest is the explanation you use when the interviewer asks you to go deeper.

Created with AI-assisted research and editorial review by Hermevia Publications

Book details and formats at Hermevia

CHAPTER 1

Q2. When ML is the wrong tool

Interview question
When is a heuristic or conventional software system preferable to ML? How would you compare expected impact with data-collection, labeling, infrastructure, and compute costs?

Interview answer: I'd reach for a plain rule-based system when the rule is stable, examples are rare, mistakes are easy to catch, or the payoff just isn't worth the setup and running costs.

Then I weigh the full cost of ML against that simple baseline: the data work, labeling, engineering, serving, monitoring, review, retraining, all of it. The real question isn't "Can ML solve this?" It's "Will learning a pattern create enough value to justify the extra complexity and risk?"

Why it matters

A simple system has real strengths: predictable, easy to explain, fails fast, low latency, usually cheaper to maintain. ML only earns its cost if it handles variation a simple rule set can't. And starting complex can create new problems: collecting labels can change how users behave, proxy targets can bake in old bias, and serving infrastructure adds failure modes a simple program never had.

The common mistake is comparing training cost against a "free" heuristic. The real comparison is cost over the whole lifecycle versus value delivered.

A practical answer

I use three gates.

1. **Solvability:** Is there a pattern beyond a few stable rules? Are examples representative at decision time? Is the label observable soon enough to learn from?
2. **Headroom:** Does the baseline leave meaningful user or business value on the table? What is the cost per unit of harm or delay?
3. **Operability:** Can the result be monitored, explained where required, rolled back, and maintained as data and behavior change?

Then I lay the comparison out side by side:

Cost or benefit	Heuristic or software system	ML system
Initial design	Rules, integration, expert review	Data work, labels, model development, serving
Runtime behavior	Deterministic and inspectable	Statistical; confidence and drift need monitoring
Edge cases	Often predictable	Unknown examples may be handled unpredictably
Maintenance	Rule updates	Rules, data, features, models, infrastructure
Scalability of logic	Can become brittle across many cases	Can generalize across cases when data supports it
Reversibility	Often simple	Rollout, shadowing, versioning, and fallback may be required

Senior depth: I wouldn't just "estimate ROI" with one made-up multiplier. I'd write down the real variables: how many decisions this touches, the expected effect per decision, what it costs to build and run, and how long until we know if it's working. Then I'd test the shakiest assumption first, cheaply. A two-week data audit might show the signal isn't even available. A quick rules prototype might show three rules already capture most of the value. Either way, that changes the decision before anyone builds a platform.

Common mistake: Defaulting to ML when a stable rule already works, or comparing ML's full lifecycle cost against a heuristic you're pretending is free.

If they ask a follow-up

When would you migrate a heuristic to ML? When the rules are breaking down or falling behind, the user base is changing, a tested pattern beats the current system, and the team can actually support the new setup. I'd keep the heuristic around as a baseline and fallback while migrating.

How do you include reputational or fairness harm? Turn it into a guardrail with a real threshold, not just a line item in a cost model. Some harms should block launch no matter how good the average return looks. I'd ask: who bears the risk, who decides what's acceptable, and how would we catch it getting worse?

What if inference cost is tiny but engineering cost is large? Engineering and maintenance still count. A cheap per-request cost doesn't mean ownership, incident response, and ongoing retraining are free. I'd weigh the team's opportunity cost as part of the real investment.

Practice

Pick a product feature you know well. Write one heuristic for it, one outcome it could improve, and the evidence that would justify swapping in ML. Add one fallback requirement. Keep it under two minutes.


CHAPTER 7

Q4. Monitoring drift without immediate labels

Interview question
How do you monitor data, feature, prediction, and model-quality drift when live labels are delayed or unavailable?

Interview answer: I'd monitor a hierarchy of signals, because no single drift metric explains production health on its own. Data monitors cover freshness, volume, schema, missingness, and value ranges. Feature monitors compare live distributions against the training reference, by segment. Prediction monitors track score distribution, confidence, saturation, and policy thresholds.

When labels are delayed, I'd lean on immediate proxy signals plus whatever delayed ground truth exists: known outcomes, human review, longer-window business metrics, partially observed tasks. Every alert needs freshness and coverage attached to it, or it can tell me the model is bad when really it just doesn't know much yet.



Illustrative signals: input and prediction drift arrive before confirmed quality labels.

Why it matters

Delays are normal in fraud, churn, health, and recommendation systems. Waiting weeks for labels can't protect the release that's live right now. And a proxy metric can go up even while real outcomes are getting worse. The operational design needs to keep **nowcasting**, **early detection**, and **retrospective evaluation** as clearly separate ideas.

A practical answer

I'd organize monitoring around what actually could have failed:

Layer	Example signals	Comparison
Ingestion	Rows, partitions, event-time lag, rejects	Expected volume and seasonality
Data quality	Nulls, invalid values, duplicate keys, schema changes	Contract and historical baseline
Features	Distribution, freshness, missingness, category rates	Training reference by segment
Predictions	Score distribution, class rate, abstention rate, output length	Expected and candidate-model ranges
Outcomes	Label-based quality and business KPIs	Released model, with maturity window
Operations	Latency, errors, saturation, dependency failures	Service objectives

The monitoring loop runs from observed production signals to diagnosis, containment, correction, and verified recovery, with every action tied back to the specific model and data versions involved.

For delayed labels, I'd use several clocks at once. A fraud decision can be checked against a chargeback proxy within days, and against the final outcome much later. A recommendation can use immediate engagement first, then return or satisfaction after a longer window. I'd record the observation window and censoring rule so incomplete outcomes never get compared against complete ones.

Thresholds should mix absolute and relative conditions. Alert when a critical invariant fails, when volume falls outside its expected range, or when a segment's average prediction moves by more than some amount and stays there. I'd avoid paging on every statistical wiggle, since noisy pages just train people to ignore the system entirely.

Senior depth: A serious observability program stores a compact prediction trace: prediction time, event-time context, model and feature versions, output, policy threshold, outcome once it's available, and experiment assignment. That supports cohort queries and lets you recompute metrics reproducibly. Netflix's own observability work makes the case for why teams need real visibility into ML pipelines and the business processes around them, not just a dashboard of model metrics.

Common mistake: Either paging on every distribution change, or waiting only for delayed labels. Both miss the layered, actionable monitoring in between.

If they ask a follow-up

What if the distribution shifts but quality does not? Treat it as a signal, not an automatic rollback trigger. Check the important segments and outcomes, confirm the change is real and actually relevant, and watch it for a predefined period. Rollback should follow real impact or credible risk, not just novelty.

Which drift metric do you trust first? None of them universally. Population stability or Wasserstein distance can flag a distributional change, while missingness or a domain invariant can be more directly actionable. I pick metrics tied to specific failure modes and check them against known incidents and outcomes.

Practice

Practice in 60 seconds: A fraud label takes 90 days to finalize, but chargebacks show up in 14. Design an immediate, an intermediate, and a mature monitoring layer, with one decision rule for each.

CHAPTER 9


Q7. Tracing a fabricated RAG answer

Interview question

A user says the assistant fabricated an answer. What traces do you inspect to separate retrieval, ranking, prompting, context, and generation failures?

Interview answer: I'd reconstruct the request as an evidence chain: source versions available at request time, parsed chunks, candidate lists, authorization decisions, final ranking, assembled context, prompt, model call, answer claims, citations, and downstream feedback. Then I'd label the first stage that actually lost the required evidence.

If the correct passage never made it into the index or candidate set, that's ingestion or retrieval. If it got in but was pushed out, that's ranking or context budgeting. If it was present and the answer still contradicted it, that's prompting, model behavior, validation, or a source conflict. I'd protect privacy along the way and avoid concluding "fabrication" from the final sentence alone.




The first failed boundary localizes retrieval, policy, assembly, or generation.

Trace the first boundary that lost evidence, authorization, context, or entailment.

Why it matters

Users experience one response, but engineering diagnosis needs a real causal trace. A weak trace often records nothing but the prompt and the final answer, which makes debugging depend on memory and pushes teams toward blanket fixes like "make the model more cautious." The first broken contract is a much better starting point than the most visible symptom.

A useful trace keeps components distinct and records decisions without needlessly duplicating sensitive content:



A request trace connects policy, retrieval, prompt, model, output, citations, cost, and outcome.

A practical answer

First, freeze the incident. Record the request ID, time, model and prompt versions, and the relevant release configuration. I wouldn't just immediately rerun against a mutable corpus without noting the source might have already changed underneath me.

Then I'd work through the stages in order:

- **Source and ingestion:** Was the document available, current, successfully parsed, and sitting in the expected ACL and tenant partition? Do the exact snippets show up in the stored chunks?
- **Retrieval:** Did the approved passage show up in any raw candidate list at all? Were query rewriting, filters, embedding versions, and lexical statistics correct?
- **Authorization:** Did a policy or tenant filter remove relevant evidence, or could missing filtering have exposed evidence to the wrong user?
- **Reranking and selection:** Did the passage fall below the cutoff, or lose out during a diversity deduplication step? Did the context builder truncate the exact sentence that mattered?
- **Prompt:** Were the system and user instructions consistent with each other? Could a retrieved instruction have outranked the intended evidence contract? Was the question transformed in a way that changed what it meant?
- **Generation:** Did the model produce claims unsupported by the context it was given? Were the claims atomic enough to inspect, or bundled into one sentence mixing supported and unsupported parts?
- **Citations:** Did the citations actually resolve, and did the cited passage support the claim next to it? A citation can exist and still be semantically unrelated.
- **Feedback quality:** Did the user's report actually refer to a different answer, language, time, or document than what's in the trace? Was the report accurate but incomplete?

Then I'd build a minimal replay from the frozen artifacts, changing one variable at a time: candidate set, context order, prompt, or model. I'd label the earliest causal break and turn it into a regression case using the user-authorized, minimally necessary data.

Senior depth: Production traces need controlled access, retention, and redaction. I'd keep a restricted diagnostic payload separate from routine logs, hash the stable IDs, and make access to any of it auditable. Since traces can hold personal or confidential content, debugging access should follow the same authorization discipline as the source corpus itself. Trace completeness needs its own monitoring too: missing stage transitions can hide exactly the failures they were supposed to help diagnose.

Common mistake: Inspecting only the final prompt after a fabricated answer shows up, when the first lost or unauthorized piece of evidence might sit much earlier in the trace.

If they ask a follow-up

What if the trace is incomplete? Say so plainly. Use independent signals like index build manifests, cache keys, model gateway logs, and whatever partial user evidence exists. Mark the diagnosis provisional, add the missing telemetry going forward, and don't overfit a fix to an incomplete reconstruction.

Who owns the incident? Ownership follows the failed boundary, not whoever happened to deploy last. Retrieval, platform, data, application, and security owners can all jointly own it if several contracts failed at once.

Practice

Design a trace schema for a RAG request. Include at least ten fields, explain which ones are safe for routine logs, and mark exactly where redaction or restricted storage kicks in.